



# MATERIAL SAFETY DATA SHEET

Revised 1

Date 05/2012 replaces 12/2010

## TOA Acrylic Wall Putty

### 1. Identification of the substance/preparation and of the company/undertaking

Product name and/or code : TOA Acrylic Wall Putty  
Type of Product : Mixture of emulsion based on acrylic, filler and additives.  
Supplier/Manufacturer : TOA PAINT (THAILAND) CO.,LTD  
31/2 Moo 3 , Bangna-Trad Rd.,KM.23 Bangsaothong.  
Amphur Bangsaothong , Samuthprakarn 10540, Thailand  
Tel : 0-2335-5555  
Fax : 0-2312-8903  
Emergency telephone number : Tel. 02-335-5555 Ext. 1260

### 2. Hazards identification

Eye Hazards : May cause eye irritation.  
Skin Hazards : May cause skin irritation.  
Ingestion Hazards : May be harmful if swallowed.  
Inhalation Hazards : May cause headache, nausea.

### 3. Composition/information on ingredients

Chemical name	CAS no.	EC Number	%	Classification
Polymer	55965-84-9	247-500-7	10 - 15	R23/24/25, R34, R43, R50/53
Filler	-	-	70 - 75	-
Water	7732-18-5	231-791-2	15 - 20	-
Others	-	-	4 - 6	-

### 4. First aid measures.

After Eye Contact : Rinse eyes thoroughly with water for at least 15 minutes. Consult physician.  
After Skin Contact : Wash skin thoroughly with soap and water. Remove contaminated clothing.  
If symptoms persist consult physician.  
After Ingestion : Do not induce vomiting. Dilute with water. Contact physician.  
After Inhalation : Remove to fresh air. If breathing has stopped, institute artificial respiration.  
Consult with physician.

### 5. Fire-fighting measures

Extinguishing media : In case of fire, use water spray (fog) foam, dry chemical, or CO<sub>2</sub>.  
Fire fighting instructions : Firefighters should wear self-contained breathing apparatus and full protective gear.



# MATERIAL SAFETY DATA SHEET

Revised 1

Date 05/2012 replaces 12/2010

## TOA Acrylic Wall Putty

### 6. Accidental release measures

- |                                    |   |
|------------------------------------|---|
| Personal protection                | : Wear suitable protective equipment.   |
| Environmental precautions          | : Prevent product entering soil, natural waters and drains.   |
| Methods for cleaning and taking up | : Contain spill, collect with absorbent material and transfer into suitable containers.<br>Avoid contact. Keep spills out of sewers and open bodies of water. |

### 7. Handling and storage

- |                                  |   |
|----------------------------------|---|
| Handling and Storage Precautions | : Store in a cool dry area. Protect from sun. Keep containers tightly closed.<br>Allow to warm to room temperature and mix well before using. |
| Work/Hygienic Practices          | : Wash thoroughly with soap and water after handling.   |

### 8. Exposure controls/personal protection

- |                        |   |
|------------------------|---|
| Engineering Controls   | : Use with adequate general and local exhaust ventilation.                              |
| Eye/Face Protection    | : Safety glasses with side shields or goggles.  |
| Skin Protection        | : Avoid skin contact. Wear long sleeve shirt and long pants. Chemical resistant gloves. |
| Respiratory protection | : General room ventilation is normally adequate.  |

### 9. Physical and chemical properties

- |                   |                                 |
|-------------------|---------------------------------|
| Appearance        | : White paste                   |
| Odor              | : Characteristic                |
| Chemical Type     | : Mixture                       |
| Physical State    | : Paste                         |
| Melting Point     | : N/AV                          |
| Boiling Point     | : N/AV                          |
| Density at 25°C   | : 1.72 – 1.74 g/cm <sup>3</sup> |
| Vapour Pressure   | : N/AV                          |
| pH Value at 25°C  | : 9.0 – 10.5                    |
| Viscosity at 25°C | : 90,000 – 120,000 cps.         |
| Vapor Density     | : > Air                         |
| Solubility        | : Dilutable                     |



# MATERIAL SAFETY DATA SHEET

Revised 1

Date 05/2012 replaces 12/2010

## TOA Acrylic Wall Putty

### 10. Stability and reactivity

Stability	: Stable
Hazardous polymerization	: Will not occur
Conditions to avoid (Stability)	: N/A
Incompatible materials	: N/A
Hazardous decomposition products	: N/A
Conditions to avoid (Polymerization)	: N/A

### 11. Toxicological information

N/A

### 12. Ecological information

Product is slightly water polluting. Do not allow to enter waste water drain, waterways or soil.

### 13. Disposal considerations

Dispose in accordance with applicable federal, state and local government regulations.

### 14. Transport information

ADR / RID	: Non dangerous goods.
IMO / IMDG	: Non dangerous goods.
IATA / ICAO	: Non dangerous goods.

### 15. Regulatory information

U.S. Regulatory information	: All ingredients of this product are listed or are excluded from listing under the U.S. Toxic Substances Control Act (TSCA) Chemical Substance Inventory
SARA Section 313 Notification	: This product does not contain any ingredients regulated under Section 313 of the Emergency Planning and Community Right-To-Know Act of 1986 or 40 CFR 372. This information must be included in all MSDS that are copied and distributed for this material.

### 16. Other information

None

Disclaimer	: These data are based on information we believe to be reliable. They are offered in good faith, but without guarantee as conditions and methods of use of our products are beyond our control. It is the purchaser's responsibility before using any product to verify this data under their own operating conditions and to determine whether the product is suitable for their purposes.
------------	---